


Specifications



Models	SLC-12		SLC-18		SLC-24	
Measurements	Metric	US	Metric	US	Metric	US
Working height:						
standard forks - forks down	3.40 m	11 ft 2 in	5.10 m	16 ft 9 in	6.78 m	22 ft 3 in
standard forks - forks up	3.94 m	12 ft 11 in	5.64 m	18 ft 6 in	7.32 m	24 ft
adjustable forks - forks down	3.40 m	11 ft 2 in	5.10 m	16 ft 9 in	6.78 m	22 ft 3 in
adjustable forks - forks up	3.94 m	12 ft 11 in	5.64 m	18 ft 6 in	7.32 m	24 ft
boom*	3.70 m	12 ft 2 in	5.41 m	17 ft 9 in	7.10 m	23 ft 3 in
A Height - stowed	2.18 m	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m	7 ft 2 in
B Length - stowed	86 cm	2 ft 10 in	86 cm	2 ft 10 in	86 cm	2 ft 10 in
A - operating	1.60 m	5 ft 3 in	1.85 m	6 ft 1 in	2.06 m	6 ft 9 in
A Width - stowed**	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in
- with stabilizers lowered	1.68 m	5 ft 6 in	1.68 m	5 ft 6 in	1.68 m	5 ft 6 in

Productivity

Load capacity:

14 in (36 cm) load center	295 kg	650 lbs	295 kg	650 lbs	295 kg	650 lbs
24 in (61 cm) load center	193 kg	425 lbs	193 kg	425 lbs	193 kg	425 lbs
42 in (107 cm) load center	82 kg	180 lbs	73 kg	160 lbs	73 kg	160 lbs
A Ground clearance	5 cm	2 in	5 cm	2 in	5 cm	2 in
Load height minimum	15 cm	6 in	15 cm	6 in	15 cm	6 in
Front casters	10 cm	4 in	10 cm	4 in	10 cm	4 in
Rear casters	13 cm	5 in	13 cm	5 in	13 cm	5 in

Power

Average cranks:

standard winch	27.8 cranks/m8.5 cranks/ft	27.8 cranks/m8.5 cranks/ft	27.8 cranks/m8.5 cranks/ft
----------------	----------------------------	----------------------------	----------------------------

Weight

Standard	102 kg	225 lbs	139 kg	307 lbs	157 kg	347 lbs
----------	--------	---------	--------	---------	--------	---------

Standards Compliance EU Directive: 2006/42/EC (Machinery)

Load Handling Attachments

Measurements	Metric	US	Weight - Metric	Weight - US
Standard forks (l/w/d)***	71/58/6 cm	28/23/2.5 in	12 kg	26.5 lbs
Adjustable forks (l/w/d)***	70/30-76/6 cm	27.5/12-30/2.5 in	24 kg	52.5 lbs
Fork extensions detached (each) (l/w/d)***	76/5/8 cm	30/2/3 in	2 kg	4.5 lbs
Fork extensions attached (each) (l/w/d)***	64/5/8 cm	25/2/3 in	2 kg	4.5 lbs
Boom (l/w/d)***	46-107/4/15 cm	18-42/1.5/6 in	18 kg	39.9 lbs
Load platform (l/w/d)***	67/58/6 cm	26.3/23/2.5 in	14 kg	31.5 lbs

* Measured from ground to bottom of shackle.

** Outside dimensions.

*** Length/Width/Depth.

Features

Standard Features

Measurements

SLC™ -12

- 3.94 m (12 ft 11 in) maximum lifting height
- Up to 295 kg (650 lbs) lift capacity

SLC-18

- 5.64 m (18 ft 6 in) maximum lifting height
- Up to 295 kg (650 lbs) lift capacity

SLC-24

- 7.32 m (24 ft) maximum lifting height
- Up to 295 kg (650 lbs) lift capacity

Productivity

- Heavy-duty design
- Strong, lightweight aluminum telescoping mast with mast brake
- Quick set up requires no tools
- Interchangeable load handling attachments
- Rear transport wheel assembly
- Glide rails allow easy loading and unloading, on or off a vehicle, for transport
- Hold-down bar secures mast assembly during transport

Power

- One speed manual winch

Easily Configured To Meet Your Needs

Productivity & Fork Options

- Standard forks
- Adjustable forks
- Fork extensions
- Boom
- Pipe cradle⁽¹⁾
- Load platform

Power Options

- One speed manual winch (standard)
- Two speed manual winch⁽¹⁾

Base Options

- Standard base
- Standard mast brake
- Stabilizer set (standard on SLC-18, -24)

Wheels & Casters

- Non-marking 10 cm (4 in) front casters (standard)
- Non-marking 13 cm (5 in) rear casters (standard)
- Side brakes (standard)

Options & Accessories

Productivity

- Adjustable forks
- Fork extensions
- Boom
- Pipe cradle⁽¹⁾
- Load platform
- Stabilizer set (option on SLC-12)

Power

- Two speed manual winch⁽¹⁾



⁽¹⁾ Available aftermarket only



CO.MA.CO S.r.l.

via XIV Strada 21 - 20020 Cesate (MI) - Italy

Tel. +39 02 99065169

info@comacopro.com

www.comacopro.com